

PURELLO FIX & CLIC RIGID SPC

Modern flooring for a practical lifestyle



PURELLO	FIX 30 V	FIX 55 V	CLIC 30 V silento
Flooring type	glue-down	glue-down	with acoustic underlay
Classification	23 – 31	33 – 42	23 – 31
Locking system	–	–	Uniclic
Total thickness	2,5 mm	2,5 mm	4 + 1 mm
Wear layer	0,30 mm	0,55 mm	0,30 mm
Dimensions	178 x 1219 mm	178 x 1219 mm	178 x 1219 mm
Weight	4,61 kg/m ²	4,61 kg/m ²	8,30 kg/m ²
Packaging	18 pcs / 3,90 m ²	18k pcs / 3,90 m ²	10 pcs / 2,17 m ²
Thermal resistance	0,0174 m ² K/W	0,0174 m ² K/W	0,0278 m ² K/W



PURELLO FIX & CLIC RIGID SPC



FIX 30 V 31128 | **CLIC 30 V silento 35128** | skirting board
FIX 55 V 51128 | 2676



FIX 30 V 31129 | **CLIC 30 V silento 35129** | skirting board
FIX 55 V 51129 | 2709



FIX 30 V 31117 | **CLIC 30 V silento 35117** | skirting board
0618



FIX 30 V 31143 | **CLIC 30 V silento 35143** | skirting board
FIX 55 V 51143 | 0622



FIX 30 V 31115 | **CLIC 30 V silento 35115** | skirting board
3172



FIX 30 V 31135 | **CLIC 30 V silento 35135** | skirting board
2572



FIX 30 V 31116 | **CLIC 30 V silento 35116** | skirting board
FIX 55 V 51116 | 2647



FIX 30 V 31131 | **CLIC 30 V silento 35131** | skirting board
2709



FIX 30 V 31141 | **CLIC 30 V silento 35141**



FIX 30 V 31144 | **CLIC 30 V silento 35144** | skirting board
FIX 55 V 51144 | 0613



FIX 30 V 31118 | **CLIC 30 V silento 35118** | skirting board
FIX 55 V 51118 | 0618



FIX 30 V 31126 | **CLIC 30 V silento 35126** | skirting board
FIX 55 V 51126 | 2433



FIX 30 V 31138 | **CLIC 30 V silento 35138** | skirting board
2655



FIX 30 V 31155 | **CLIC 30 V silento 35155** | skirting board
FIX 55 V 51155 | 0623



FIX 30 V 31110 | **CLIC 30 V silento 35110** | skirting board
2755



FIX 30 V 31124 | **CLIC 30 V silento 35124** | skirting board
0627

Accessories



Skirting board PURELLO USL 60
Dimensions: 6 x 1,5 x 250 cm
Packaging: 25 m




Modern flooring for a practical lifestyle



PURELLO

FIX 30 V / FIX 55 V



Tiles with high dimensional accuracy are made with standard LVT technology from multiple layers of vinyl.

For a gluedown installation on prepared base Schönox Durocol adhesive is recommended.

PURELLO

CLIC 30 V silento RIGID SPC



Rigid planks with high dimensional accuracy are made with the most modern extruded **RIGID SPC** technology from pure vinyl and limestone. Planks are **dimensionally accurate** even with significant changes in flooring temperatures.

Silento – integrated underlay from acoustic foam of 1 mm height easily adheres to the smooth base (no additional underlays needed).

Patented **Uniclic** locking system is **very precise and strong**. Planks are being easily and quickly installed as a floating floor with no need for fixation.



Excellent price quality ratio

PURELLO vinyl floors achieve **superior quality** compared to usual offer on the market.



Healthy environment

PURELLO vinyl floors fulfill hygienic requirements of valid European standards. Does not contain any recycled materials or **phthalate plasticizers**.



Long lifetime and easy maintenance

PURELLO vinyl flooring is **even more durable and easier to clean** thanks to PUR surface treatment, saving water consumption, energies and cleaning agents in the process.



Authentic decors

PURELLO decors have natural wooden appearance with **perfect reproduction of oak trees** in both natural and trending shades. The fine surface embossing together with slightly beveled edges enhance true illusion of natural design.



Very low thermal resistance

PURELLO vinyl tiles do not prevent heat transfer from **floor heating**. When installing on heated floors, the usual principles are being applied.



Proven areas of use

PURELLO vinyl tiles are suitable for all types of **high-traffic residential areas and commercial areas with moderate-traffic**.

PURELLO FIX & CLIC RIGID SPC

